

10/567596

1AP20 Rec'd POT/PTO 06 FEB 2006

"MASTER-KEYED PIN TUMBLER LOCK WITH RELATIVE  
MASTER-KEY"

DESCRIPTION

This invention deals with a master-keyed pin tumbler lock with  
5 relative master-key.

In particular, the master-keyed pin tumbler lock is  
exchangeable and removable, using an extraction key.

Pin tumbler locks are already known, and even removable pin  
tumbler locks (extractable using an extraction key). Spanish Utility  
10 Model 1009297 and Patents US2829513 and US1328074, for example,  
are clear precedents that form part of the current state of the technique.

Document US 2 358 164 A, describes a combination of a pin  
tumbler lock and a key, which has a notch on one its sides whose  
minimum width is the distance between the maximum level reached by  
15 the projections of the pins that move in one direction and the maximum  
level reached by the projections of the pins that move in the opposite  
direction. According to this document each pin also has an inner  
window, another projection placed on the opposite side to that of the  
inner projection and on the other side, the key has a notch, which  
20 combines with the projections of the inner windows of the pins. In  
another execution all the projections are replaced with grooves or steps  
and one side of the key has double serration and the other side is  
smooth.

The main aim of the invention is to "master-key" the pins of  
25 the pin tumbler lock.

The relative master-key is also a main aim of the invention, to operate the pin tumbler lock with the "master-keyed" pins.

An additional aim of the invention is for this master-keyed pin tumbler lock to be extractable using a master extraction key

5           The key for use is a dual open wave one and it is reversible.

According to the invention, the master-keyed pin tumbler lock, with each pin having an inner window with an outer protuberance upon which a spring acts, and an inner projection on which the key acts, giving rise to the movement of the pin, and the inner projections being at  
10 different heights and the pins placed so that some move in one direction and others in the opposite direction, is characterised because each pin has a step on its inner window placed on the opposite side to that of the inner projection.

According to the invention, the master key:

15           a) has a wave on one of its sides, whose minimum width is the distance between the maximum level reached by the projections of the pins that move in one direction and the maximum level reached by the projections of the pins that move in the opposite direction;

            b) on the opposite side, it has a wave with double serration  
20 combined with the steps of the inner windows of the pins.

In order to understand the subject of this invention better, a preferential form of practical execution is illustrated on the drawings, subject to incidental changes that take nothing away from its foundation.

Figure 1 shows a traditional pin tumbler lock (1) (side view and  
25 front view).

Figure 2 shows both a -left (2a)/right (2b)- pin in its relative positions and a traditional key (3) .

Figure 3 shows a similar view to figure 2, but of a practical execution of the subject of the invention, with a -left (2'a)—right (2'b)-  
5 pin and its master key (3').

Figure 4 shows a front and rear perspective view of the master key (3) of figure 3 subject of the invention.

Locks that have a tumbler (1) with a plurality of cavities (10) are already known, where there are self-retained pins (2), some of which  
10 (2a) act in the opposite direction to the others (2b).

The pins (2) are of the kind that have an outer protuberance (21) which a spring (m) acts upon and an inner window (20) with an inner projection (22).

The inner projection (22) of each pin (2) is at the  
15 same/different height (h) with respect to an imaginary axis (e).

The traditional key (3) has some protuberances (3) in the channel (31) of each side, combined with the respective inner projections (22) of the pins (2) so that when the key (3) is inserted into the windows (20), the pins (2) move making it possible to open the lock .

20 In agreement with the invention, two pins (2') are placed for each working channel (10) one left (2'a) and other right (2'b) placed in such a way in the channel (10) that one (2'a) acts in the opposite direction to the other (2'b).

In agreement with the invention, each pin (2'a), (2'b) has a step (23) in its inner window (20') placed on the opposite side to that of the inner projection (22').

These steps (23) are placed in the pins (2') at different heights  
5 (h<sub>3</sub>) with respect to the imaginary axis (e).

The pins (2') have been shown in figure 3 with the projections (22') further away from the imaginary axis (e) so that the sum of the absolute values of the heights (h<sub>1</sub>), (h<sub>2</sub>) with respect to this imaginary axis have a maximum of: (h<sub>1</sub> + h<sub>2</sub>) max.

10 The master key (3') has a channel/wave (31') on one of its sides, whose minimum width (d<sub>1</sub>) is, at least, equal to the distance between the maximum level (h<sub>1</sub>) reached by the projections (22') of the pins (2'a) that move in one direction and the maximum level (h<sub>2</sub>) reached by the projections (22') of the pins (2b) that move in the opposite  
15 direction:  $d_1 > (h_1 + h_2)$ .

With this channel/wave (31'), when key (3') is inserted into the window (20') it covers all the internal projections (22') of all the pins (2').

In figure 3 the channel/wave (31) has an even width (d<sub>1</sub>).

20 On the other side, the master key (3') also has a wave (32) with double serration (30') combined with the steps (23) of the inner windows (20') of the pins (2'a), (2'b); thus, on this side, the wave (32) has the possibilities of a traditional key with respect to the steps (23).

The drum lock (1) has an additional retaining channel (10')  
25 where there is an additional pin, for retaining the drum lock (1). This

additional pin is activated by a special master key –not shown- which has the same size and shape as the master key (3'), but which has different (supplementary) cutwork, to be able to act upon this retaining pin and be able to extract the drum lock (1).